

**PRODUCT** : LCD MODULE**MODEL NO.** : TFT1N5182-V1-E**SUPPLIER** : TRULY SEMICONDUCTORS LTD.**DATE** : July 12, 2010CERT. No. QAC0946535  
(ISO9001)CERT. No. HKG002005  
(ISO14001)

# SPECIFICATION

Revision: 1.2

**TFT1N5182-V1-E**

This module uses ROHS material

If there is no special request from customer, TRULY SEMICONDUCTORS LTD., will not reserve the tooling of the product under the following conditions:

1. There is no response from customer in two years after TRULY SEMICONDUCTORS LTD., submit the samples;

2. There is no order in two years after the latest mass production.

And correlated data (include quality record) will be reserved one year more after tooling was discarded.

**TRULY SEMICONDUCTORS LTD:****CUSTOMER:**

Quality Assurance Department: \_\_\_\_\_

Approved by: \_\_\_\_\_

Technical Department: \_\_\_\_\_

Approved by: \_\_\_\_\_

[illegible]

# CONTENTS

- GENERAL INFORMATION
- EXTERNAL DIMENSIONS
- ABSOLUTE MAXIMUM RATINGS
- ELECTRICAL CHARACTERISTICS
- ELECTRO-OPTICAL CHARACTERISTICS
- INTERFACE DESCRIPTION
- APPLICATION CIRCUIT
- INITIAL CODE
- RELIABILITY TEST
- INSPECTION CRITERION
- PRECAUTIONS FOR USING LCD MODULES
- USING LCD MODULES
- PRIOR CONSULT MATTER
- FACTORY CONTACT INFORMATION

WRITTEN BY	CHECKED BY	APPROVED BY
HUANG YAN XUE	WANG DONG	WU SU

**■ GENERAL INFORMATION**

Item	Contents	Unit
LCD type	TFT/TRANSMISSIVE	/
Viewing direction	3:00 O' Clock	9:00O' Clock(Good viewing)
Module area (W × H×T)	47.66×80.90×3.20	mm <sup>3</sup>
Viewing area (W×H)	43.76×71.60	mm <sup>2</sup>
Active area (W×H)	41.76×69.60	mm <sup>2</sup>
Number of Dots	240(RGB)×400	/
Pixel pitch (W × H)	0.174×0.174	mm <sup>2</sup>
Driver IC	R61509V	/
Colors	262K	/
Backlight Type	LED	/
Module Power consumption	244	mw
Interface Type	System parallel interface	/
Input voltage	2.8	V

### 接口定义:

导电极布差不多中间位置有一  
条虚断线,用于贴附对位!!  
!通过虚断线对位导电布到  
弯折侧面铁架边缘,建议先用  
压力压紧避开模块侧扣位、  
TPC玻璃边缘,然后再弯折贴  
附模块背面部分的导电布!!  
谢谢!!

TP接口定义:




**DIAGRAM:**



NOTES:

1. DISPLAY TYPE: 262K TFT, TRANSMISSIVE
2. OPERATING TEMP: -10°C ~ 60°C
3. STORAGE TEMP: -20°C ~ 70°C
4. LCD DRIVER: R6T509V
5. BACKLIGHT: 4CHIP-WHITE LED, PARALLEL CONNECTION
6. ROWS COMPLIANCY
7. Vands: 模块可视区域, 建议外壳可视区域比Vands单壳小0.3mm以上
8. 客户面壳亮斑TP位置应保证与TP V.A有向外0.4MM的距离
9. TP边缘不能接触导电
10. TPVA向内1.5MM为划写可靠有效区域

CUSTOMER APPROVE		AMEND		液晶显示模块	<b>TRULY SEMICONDUCTORS LTD.</b>		
Mechanical	Electrical	Δ	更改导电布	20100614	PRODUCT NO.	DRAW NO.	REV
		Δ	更改导电布规格	20100611	TFTN5182-V1-E	CSZMDS6518	Q
		Δ	更改单面粘铜箔	20100610	DWN 钟武发	DSN	钟武发
		Δ	增加铁架压盖	20100629	CHKD 胡爱兰	APPD	黄英群
		NO.	CONTENT	DATE	 NOT IN SCALE UNIT mm SHEET: 1/1		

## ■ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Min	Max	Unit
Supply voltage for logic	V <sub>CC</sub> /IOV <sub>CC</sub>	-0.3	4.6	V
Input voltage	V <sub>IN</sub>	-0.3	IOV <sub>CC</sub> +0.3	V
Operating temperature	T <sub>op</sub>	-10	60	°C
Storage temperature	T <sub>ST</sub>	-20	70	°C
Humidity	RH	-	90%(Max60 °C)	RH

## ■ELECTRICAL CHARACTERISTICS

### DC CHARACTERISTICS

Parameter	Symbol	Min	Typ	Max	Unit
Supply voltage for logic	V <sub>CC</sub>	2.7	2.8	2.9	V
I/O power supply	IOV <sub>CC</sub>	1.7/2.7	1.8/2.8	1.9/2.9	V
Input Current	I <sub>CC</sub>	-	9.3	18.6	mA
Input voltage 'H' level	V <sub>IH</sub>	0.8IOV <sub>CC</sub>	-	IOV <sub>CC</sub>	V
Input voltage 'L' level	V <sub>IL</sub>	-0.3	-	0.15IOV <sub>CC</sub>	V
Output voltage 'H' level	V <sub>OH</sub>	0.8IOV <sub>CC</sub>	-	-	V
Output voltage 'L' level	V <sub>OL</sub>	-	-	0.2IOV <sub>CC</sub>	V

## ■ TIMING OF POWER SUPPLY

PLEASE REFER TO THE DRIVER IC SPECIFICATION.

## ■ BACKLIGHT CHARACTERISTICS

Item	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward voltage	Vf	3.0	3.2	3.4	V	If=60mA Ta=25℃
Luminance	Lv	2000	2500	3000	cd/m <sup>2</sup>	
Number of LED	4				Piece	
Connection mode	P	Parallel				

Using condition: constant current driving method If=60mA (+/-10%).

## ■ELECTRO-OPTICAL CHARACTERISTICS

Item	Symbol	Condition	Min	Typ	Max	Unit	Remark	Note
Response time	Tr +Tf	$\theta=0^\circ$ $\varnothing=0^\circ$ $T_a=25^\circ\text{C}$	-	23	35	ms	FIG 1.	4
Contrast ratio	Cr		300	662	-	---	FIG 2.	1
Luminance uniformity	$\delta$ WHITE		80	90	-	%	FIG 2.	3
Surface Luminance	Lv		154	193	-	cd/m <sup>2</sup>	FIG 2.	2
Viewing angle range	$\theta$	$\varnothing = 90^\circ$	70	80	-	deg	FIG 3.	6
		$\varnothing = 270^\circ$	70	80	-	deg	FIG 3.	
		$\varnothing = 0^\circ$	70	80	-	deg	FIG 3.	
		$\varnothing = 180^\circ$	70	80	-	deg	FIG 3.	
CIE (x, y) chromaticity	Red x	$\theta=0^\circ$ $\varnothing=0^\circ$ $T_a=25^\circ\text{C}$	0.5610	0.6110	0.6610	-	FIG 2.	5
	Red y		0.2982	0.3482	0.3982			
	Green x		0.2798	0.3298	0.3798			
	Green y		0.5139	0.5639	0.6139			
	Blue x		0.0936	0.1436	0.1936			
	Blue y		0.0187	0.0687	0.1187			
	White x		0.2316	0.2916	0.3516			
	White y		0.2306	0.2906	0.3506			

Note 1. Contrast Ratio(CR) is defined mathematically as For more information see FIG 2.:

$$\text{Contrast Ratio} = \frac{\text{Average Surface Luminance with all white pixels (P}_1, \text{P}_2, \text{P}_3, \text{P}_4, \text{P}_5)}{\text{Average Surface Luminance with all black pixels (P}_1, \text{P}_2, \text{P}_3, \text{P}_4, \text{P}_5)}$$

Note 2. Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see FIG 2.

$$L_v = \text{Average Surface Luminance with all white pixels (P}_1, \text{P}_2, \text{P}_3, \text{P}_4, \text{P}_5)$$

Note 3. The uniformity in surface luminance,  $\delta$  WHITE is determined by measuring luminance at each test position 1 through 5, and then dividing the maximum luminance of 5 points luminance by minimum luminance of 5 points luminance. For more information see FIG 2.

$$\delta \text{ WHITE} = \frac{\text{Minimum Surface Luminance with all white pixels (P}_1, \text{P}_2, \text{P}_3, \text{P}_4, \text{P}_5)}{\text{Maximum Surface Luminance with all white pixels (P}_1, \text{P}_2, \text{P}_3, \text{P}_4, \text{P}_5)}$$


Note 4. Response time is the time required for the display to transition from White to black(Rise Time, Tr) and from black to white(Decay Time, Tf). For additional information see FIG 1. The test equipment is Autronic-Melchers's ConoScope. Series

Note 5. CIE (x, y) chromaticity, The x,y value is determined by measuring luminance at each test position 1 through 5, and then make average value



Note 6. Viewing angle is the angle at which the contrast ratio is greater than 2. For TFT module the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

Note 7. For Viewing angle and response time testing, the testing data is base on Autronic-Melchers's ConoScope. Series Instruments. For contrast ratio, Surface Luminance, Luminance uniformity, CIE The test data is base on TOPCON's BM-5 photo detector.

Note 8. For TFT module, Gray scale reverse occurs in the direction of panel viewing angle.

**FIG.1. The definition of Response Time**

**FIG.2. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x, y) chromaticity**

A : 5 mm  
 B : 5 mm  
 H, V : Active Area  
 Light spot size  $\varnothing=5\text{mm}$ , 500mm distance from the LCD surface to detector lens  
 measurement instrument is TOPCON's luminance meter BM-5


**FIG.3. The definition of viewing angle**




**■ INTERFACE DESCRIPTION**

Pin NO.	Name	I/O or connect to	DESCRIPTION	When not in use
1	YU	-	Touch panel coordinate in the up side of envisage drawing.	OPEN
2	XL	-	Touch panel coordinate in the left side of envisage drawing.	OPEN
3	YD	-	Touch panel coordinate in the down side of envisage drawing.	OPEN
4	XR	-	Touch panel coordinate in the right side of envisage drawing.	OPEN
5	GND	0V	Power Ground	-
6	VCC	2.8V	Power supply to the liquid crystal power supply analog circuit.	-
7	IOVCC	1.8/2.8V	Power supply to the interface pins	-
14	NC	-	No connection.	-
9	TE	O	Frame head pulse. (Amplitude: IOVCC-GND) FMARK is used when writing data to the internal RAM.	OPEN
10	RDX	I	Read strobe signal .	IOVCC
11	WRX	I	Write strobe signal .	IOVCC
12	DCX	I	Register select signal.	IOVCC
13	CSX	I	Chip select signal.	IOVCC
14	NC	-	No connection.	-
15	DB10	I/O	Data bus	GND or IOVCC
16	DB11	I/O	Data bus	GND or IOVCC
17	DB12	I/O	Data bus	GND or IOVCC
18	DB13	I/O	Data bus	GND or IOVCC
19	DB14	I/O	Data bus	GND or IOVCC
20	DB15	I/O	Data bus	GND or IOVCC
21	DB16	I/O	Data bus	GND or IOVCC
22	DB17	I/O	Data bus	GND or IOVCC
23	NC	-	No connection.	-
24	NC	-	No connection.	-
25	NC	-	No connection.	-
26	NC	-	No connection.	-
27	NC	-	No connection.	-
28	NC	-	No connection.	-
29	NC	-	No connection.	-
30	NC	-	No connection.	-
31	NC	-	No connection.	-
32	NC	-	No connection.	-
33	NC	-	No connection.	-
34	NC	-	No connection.	-
35	NC	-	No connection.	-
36	NC	-	No connection.	-
37	NC	-	No connection.	-
38	RESET	I	Reset signal.	-
39	NC	-	No connection.	-

40	NC	-	No connection.	-
41	NC	-	No connection.	-
42	LEDA	-	LED light,anode.	OPEN
43	LEDK1	-	LED Light,cathode.	OPEN
44	LEDK2	-	LED Light,cathode.	OPEN
45	LEDK3	-	LED Light,cathode.	OPEN
46	LEDK4	-	LED Light,cathode.	OPEN

## ■ APPLICATION CIRCUIT

Please consult our technical department for detail information.

## ■ INITIAL CODE


Please consult our technical department for detail information.

**■ RELIABILITY TEST**

No.	Test Item	Test Condition	Inspection after test
1	High Temperature Storage	70±2℃/200 hours	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 1.Air bubble in the LCD; 2.Sealleak; 3.Non-display; 4.missing segments; 5.Glass crack; 6.Current Idd is twice higher than initial value. 7. The surface shall be free from damage. 8.Linearity must be no more than 1.5% by the linearity tester. 9..The Electric characteristics requirements shall be satisfied.
2	Low Temperature Storage	-20±2℃/200 hours	
3	High Temperature Operating	60±2℃/120 hours	
4	Low Temperature Operating	-10±2℃/120 hours	
5	Temperature Cycle	-10±2℃~25~60±2℃×10cycles	
6	Damp Proof Test	50℃±5℃×90%RH/120 hours	
7	Vibration Test	Frequency: 10Hz~55Hz~10Hz Amplitude: 1.5mm, X, Y, Z direction for total 3hours (Packing condition)	
8	Drooping test	Drop to the ground from 1m height, one time, every side of carton. (Packing condition)	
9	ESD test	Voltage:±8KV R: 330Ω C: 150pF Air discharge, 10time	
10	Hitting test	1,000,000 times in the same point, Hitting pad: tip R3.75 mm,Silicone rubber, Hardness:40 deg.; Load: 2.45N; Hitting speed: Twice/sec; Electric load: None; Test area should be at 1.8 mm inside of insulation.	
11	Pen sliding durability test	100, 000 times minimum Hitting pad: tip R0.8 mm Plastic pen; Load: 1.47N; Sliding speed: 60 mm/sec; Electric load: None Test area should be at 1.8 mm inside of insulation.	
Remark: 1.The test samples should be applied to only one test item. 2.Sample size for each test item is 5~10pcs. 3.For Damp Proof Test, Pure water(Resistance>10MΩ) should be used. 4.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judge as a good part. 5.EL evaluation should be excepted from reliability test with humidity and temperature: Some defects such as black spot/blemish can happen by natural chemical reaction with humidity and Fluorescence EL has. 6.Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.			


## ■ INSPECTION CRITERION





<b>TRULY®</b> OUTGOING QUALITY STANDARD	PAGE 1 OF 7
TITLE:FUNCTIONAL TEST & INSPECTION CRITERIA	MDS Product
<p>This specification is made to be used as the standard acceptance/rejection criteria for Color mobile phone LCM with touch panel.</p> <p>1 Sample plan</p> <p>Sampling plan according to GB/T2828.1-2003/ISO 2859-1: 1999 and ANSI/ASQC Z1.4-1993, normal level 2 and based on:</p> <p>Major defect: AQL 0.65</p> <p>Minor defect: AQL 1.5</p> <p>2. Inspection condition</p> <p>Viewing distance for cosmetic inspection is about 30cm with bare eyes, and under an environment of 20~40W light intensity, all directions for inspecting the sample should be within 45° against perpendicular line.</p> <p>3. Definition of inspection zone in LCD.</p> <div data-bbox="522 1079 1008 1295" data-label="Diagram"> </div> <p>Zone A: character/Digit area</p> <p>Zone B: viewing area except Zone A (ZoneA+ZoneB=minimum Viewing area)</p> <p>Zone C: Outside viewing area (invisible area after assembly in customer's product)</p> <p>Fig.1 Inspection zones in an LCD.</p> <p>Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble for quality and assembly of customer's product.</p>	

TRULY® OUTGOING QUALITY STANDARD		PAGE 2 OF 7			
TITLE:FUNCTIONAL TEST & INSPECTION CRITERIA		MDS Product			
4. Inspection standards					
4.1 Major Defect					
Item No	Items to be inspected	Inspection Standard	Classification of defects		
4.1.1	All functional defects	1) No display 2) Display abnormally 3) Missing vertical, horizontal segment 4) Short circuit 5) Back-light no lighting, flickering and abnormal lighting.	Major		
4.1.2	Missing	Missing component			
4.1.3	Outline dimension	Overall outline dimension beyond the drawing is not allowed.			
4.1.4	linearity	No more than 1.5%			
4.2 Cosmetic Defect					
Item No	Items to be inspected	Inspection Standard	Classification of defects		
4.2.1	Clear Spots  Black and white Spot defect  Pinhole,  Foreign Particle,  polarizer Dirt	For dark/white spot, sizeΦ is defined as $\Phi = \frac{(x+y)}{2}$ 	Minor		
		1.			
		Zone Size(mm)		Acceptable Qty	
		A		B	C
		Φ ≤0.1		Ignore	
		0.10 < Φ ≤0.15	2		
		0.15 < Φ ≤0.20	1		
		0.20 < Φ	0		
	Clear Spots  TP Dirt	2.		Minor	
		Zone Size(mm)	Acceptable Qty		
		A	B		C
		Φ ≤0.1	Ignore		
		0.10 < Φ ≤0.15	3		
		0.15 < Φ ≤0.25	2		
		0.25 < Φ	0		

TRULY® OUTGOING QUALITY STANDARD				PAGE 3 OF 7																							
TITLE: FUNCTIONAL TEST & INSPECTION CRITERIA				MDS Product																							
	<div>Dim Spots</div> <div>Circle shaped and dim edged defects</div>	3. <table><tr><th rowspan="2">2. Zone Size(mm)</th><th colspan="3">Acceptable Qty</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>Φ ≤0.2</td><td colspan="2">Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>0.20 &lt; Φ ≤0.40</td><td colspan="2">2</td></tr><tr><td>0.40 &lt; Φ ≤0.60</td><td colspan="2">1</td></tr><tr><td>0.60 &lt; Φ</td><td colspan="2">0</td></tr></table>					2. Zone Size(mm)	Acceptable Qty			A	B	C	Φ ≤0.2	Ignore		Ignore	0.20 < Φ ≤0.40	2		0.40 < Φ ≤0.60	1		0.60 < Φ	0		Minor
2. Zone Size(mm)	Acceptable Qty																										
	A	B	C																								
Φ ≤0.2	Ignore		Ignore																								
0.20 < Φ ≤0.40	2																										
0.40 < Φ ≤0.60	1																										
0.60 < Φ	0																										
4.2 Cosmetic Defect																											
Item No	Items to be inspected	Inspection Standard				Classification of defects																					
4.2.2	Line defect Black line, White line, Foreign material on polarizer	size(mm)		Acceptable Qty			Minor																				
		L(Length)	W(Width)	zone																							
				A	B	C																					
		Ignore	W ≤0.02	Ignore		Ignore																					
		L ≤3.0	0.02 < W ≤0.03	2																							
		L ≤2.0	0.03 < W ≤0.05	1																							
		0.05 < W	Define as spot defect																								
	Foreign material on TP film	The line can be seen after mobile phone in the operating condition:						Minor																			
		size(mm)		Acceptable Qty																							
		L(Length)	W(Width)	zone																							
				A	B	C																					
		Ignore	W ≤0.03	Ignore		Ignore																					
		L ≤5.0	0.03 < W ≤0.05	3																							
		0.05 < W	Define as spot defect																								
If the scratch can be seen after mobile phone cover assembling or in the operating condition, judge by the line defect of 4.2.2. If the scratch can be seen only in non-operating condition or some special angle, judge by the following.																											

TRULY® OUTGOING QUALITY STANDARD				PAGE 4 OF 7			
TITLE:FUNCTIONAL TEST & INSPECTION CRITERIA				MDS Product			
4.2.3	Dim line defect  Polarizer scratch TP film scratch	Size(mm)		Acceptable Qty			Minor
		L(Length)	W(Width)	Zone			
				A	B	C	
		Ignore	$W \leq 0.03$	Ignore		Ignore	
		$5.0 < L \leq 10.0$	$0.03 < W \leq 0.05$	2			
		$L \leq 5.0$	$0.05 < W \leq 0.08$	1			
			$0.08 < W$	0			
4.2.4	Polarize Air bubble	Air bubbles between glass & polarizer					Minor
		2. Zone Size(mm)	Acceptable Qty				
			A	B	C		
		$\Phi \leq 0.2$	Ignore		Ignore		
		$0.20 < \Phi \leq 0.30$	2				
		$0.30 < \Phi \leq 0.50$	1				
		$0.50 < \Phi$	0				

4.3. Cosmetic Defect									
Item No	Items to be inspected	Inspection Standard	Classification of defects						
		<div>(i) Chips on corner A:LCD Glass defect</div> <div></div> <div><table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤2.0</td><td>≤S</td><td>Disregard</td></tr></table></div> <div>Notes: S=contact pad length Chips on the corner of terminal shall not be allowed to extend into the ITO pad or expose perimeter seal.</div>	X	Y	Z	≤2.0	≤S	Disregard	Minor
X	Y	Z							
≤2.0	≤S	Disregard							

TRULY® OUTGOING QUALITY STANDARD			PAGE 5 OF 7							
TITLE:FUNCTIONAL TEST & INSPECTION CRITERIA			MDS Product							
4.3.5	Glass defect	B:TP Glass defect								
										
		<table><tr><td>X(mm)</td><td>Y(mm)</td><td>Z(mm)</td></tr><tr><td>≤3.0</td><td>≤3.0</td><td>Disregard</td></tr></table>			X(mm)	Y(mm)	Z(mm)	≤3.0	≤3.0	Disregard
		X(mm)	Y(mm)	Z(mm)						
		≤3.0	≤3.0	Disregard						
(ii)Usual surface cracks										
A:LCD Glass defect										
										
		<table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0</td><td>&lt;Inner border line of the seal</td><td>Disregard</td></tr></table>			X	Y	Z	≤3.0	<Inner border line of the seal	Disregard
X	Y	Z								
≤3.0	<Inner border line of the seal	Disregard								
		B:TP Glass defect								
										
		<table><tr><td>X(mm)</td><td>Y(mm)</td><td>Z(mm)</td></tr><tr><td>≤6.0</td><td>&lt;2.0</td><td>Disregard</td></tr></table>			X(mm)	Y(mm)	Z(mm)	≤6.0	<2.0	Disregard
X(mm)	Y(mm)	Z(mm)								
≤6.0	<2.0	Disregard								
		(iii) Crack								
		Cracks tend to break are not allowed.								
										
		Major								








TITLE:FUNCTIONAL TEST &amp; INSPECTION CRITERIA

MDS Product

**4.4 Parts Defect**

Item No	Items to be inspected	Inspection Standard	Classification of defects
	4.4.1 Parts contraposition	1、 Not allow IC and FPC/heat-seal lead width is more than 50% beyond lead pattern. 2、 Not allow chip or solder component is off center more than 50% of the pad outline.	Major
	4.4.2 SMT	According to the <Acceptability of electronic assemblies> IPC-A-610C class 2 standard. Component missing or function defect are Major defect, the others are Minor defect.	

<p><b>TRULY</b><sup>®</sup> OUTGOING QUALITY STANDARD</p>		<p>PAGE 7 OF 7</p>	
<p>TITLE: FUNCTIONAL TEST &amp; INSPECTION CRITERIA</p>		<p>MDS Product</p>	
<p>4.4.3 TP Defect</p>	<p>1、 Pattern font: Pattern fonts are clear and symmetrical, pattern fonts filter lightly are allowed; The fort line is not allow to thinner or thicker than 1/3of normal size, and swing is not more than 0.1mm. the line is smooth and not broken.</p>  <p>图案字体 Pattern font</p> <p>2、 The wing forward in the side of Visual Area: The length of wing forward inside of the Visual Area: <math>n \leq 0.2\text{mm}</math>; Not excess 3 point, and the distance <math>D \geq 20\text{mm}</math>.</p>  <p>3、 Film impression: With operation, must be invisibility.</p> <p>4、 Touch panel knob: if writing function normally, it could be allowed.</p>  <p>TP鼓 TP knob</p> <p>5、 Newton ring Without operation, the color circle of Regularity or Non-regularity from the normal or slope angle of view.</p> <p>1、 <b>Regularity:</b> The area of the newton ring is less than 1/3 area of the touch panel; and no character affected and line distorted after touch panel lightening. It's ok.</p> <p>2、 <b>Non-regularity :</b> The area of the Newton ring is less than the 1/2 area of touch panel with lightening. And no character affected and line</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>规律形</p> </div> <div style="text-align: center;">  <p>非规律形</p> </div> </div>	<p>Minor</p>	

## ■ PRECAUTIONS FOR USING LCD MODULES

### Handling Precautions

(1) The display panel is made of glass and polarizer. As glass is fragile. It tends to become or chipped during handling especially on the edges. Please avoid dropping or jarring. Do not subject it to a mechanical shock by dropping it or impact.

(2) If the display panel is damaged and the liquid crystal substance leaks out, be sure not to get any in your mouth. If the substance contacts your skin or clothes, wash it off using soap and water.

(3) Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary. Do not touch the display with bare hands. This will stain the display area and degraded insulation between terminals (some cosmetics are determined to the polarizer).

(4) The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully. Do not touch, push or rub the exposed polarizers with anything harder than an HB pencil lead (glass, tweezers, etc.). Do not put or attach anything on the display area to avoid leaving marks on. Condensation on the surface and contact with terminals due to cold will damage, stain or dirty the polarizer. After products are tested at low temperature they must be warmed up in a container before coming is contacting with room temperature air.

(5) If the display surface becomes contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If it is heavily contaminated, moisten cloth with one of the following solvents

- Isopropyl alcohol
- Ethyl alcohol

Do not scrub hard to avoid damaging the display surface.

(6) Solvents other than those above-mentioned may damage the polarizer. Especially, do not use the following.

- Water
- Ketone
- Aromatic solvents

Wipe off saliva or water drops immediately, contact with water over a long period of time may cause deformation or color fading. Avoid contacting oil and fats.

(7) Exercise care to minimize corrosion of the electrode. Corrosion of the electrodes is accelerated by water droplets, moisture condensation or a current flow in a high-humidity environment.

(8) Install the LCD Module by using the mounting holes. When mounting the LCD module make sure it is free of twisting, warping and distortion. In particular, do not forcibly pull or bend the I/O cable or the backlight cable.

(9) Do not attempt to disassemble or process the LCD module.

(10) NC terminal should be open. Do not connect anything.

(11) If the logic circuit power is off, do not apply the input signals.

(12) Electro-Static Discharge Control, Since this module uses a CMOS LSI, the same careful attention should be paid to electrostatic discharge as for an ordinary CMOS IC. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

- Before remove LCM from its packing case or incorporating it into a set, be sure the module and your body have the same electric potential. Be sure to ground the body when handling the LCD modules.

- Tools required for assembling, such as soldering irons, must be properly grounded. make certain the AC power source for the soldering iron does not leak. When using an electric screwdriver to attach LCM, the screwdriver should be of ground potentiality to minimize as much as possible any transmission of electromagnetic waves produced sparks coming from the commutator of the motor.

- To reduce the amount of static electricity generated, do not conduct assembling and other work under dry conditions. To reduce the generation of static electricity be careful that the air in the work is not too dried. A relative humidity of 50%-60% is recommended. As far as possible make the electric potential of your work clothes and that of the work bench the ground potential

- The LCD module is coated with a film to protect the display surface. Exercise care when peeling off this protective film since static electricity may be generated

(13) Since LCM has been assembled and adjusted with a high degree of precision, avoid applying excessive shocks to the module or making any alterations or modifications to it.

- Do not alter, modify or change the shape of the tab on the metal frame.

- Do not make extra holes on the printed circuit board, modify its shape or change the positions of components to be attached.

- Do not damage or modify the pattern writing on the printed circuit board.

- Absolutely do not modify the zebra rubber strip (conductive rubber) or heat seal connector.

- Except for soldering the interface, do not make any alterations or modifications with a soldering iron.

- Do not drop, bend or twist LCM.

**Handling precaution for LCM**


LCM is easy to be damaged. Please note below and be careful for handling.

**Correct handling:**

As above picture, please handle with anti-static gloves around LCM edges.

**Incorrect handling:**


Please don't touch IC directly.




Please don't stack LCM.




Please don't hold the surface of panel.



Please don't stretch interface of output, such as FPC cable.



Please don't hold the surface of IC.



Please don't operate with sharp stick such as pens.

**Storage Precautions**

When storing the LCD modules, the following precaution is necessary.

- (1) Store them in a sealed polyethylene bag. If properly sealed, there is no need for the dessicant.
- (2) Store them in a dark place. Do not expose to sunlight or fluorescent light, keep the temperature between 0°C and 35°C, and keep the relative humidity between 40%RH and 60%RH.
- (3) The polarizer surface should not come in contact with any other objects. (We advise you to store them in the anti-static electricity container in which they were shipped.

**Others**

Liquid crystals solidify under low temperature (below the storage temperature range) leading to defective orientation or the generation of air bubbles (black or white). Air bubbles may also be generated if the module is subject to a low temperature.

If the LCD modules have been operating for a long time showing the same display patterns, the display patterns may remain on the screen as ghost images and a slight contrast irregularity may also appear. A normal operating status can be regained by suspending use for some time. It should be noted that this phenomenon does not adversely affect performance reliability.

To minimize the performance degradation of the LCD modules resulting from destruction caused by static electricity etc., exercise care to avoid holding the following sections when handling the modules.


- Exposed area of the printed circuit board.
- Terminal electrode sections.

## ■ USING LCD MODULES

### Installing LCD Modules

The hole in the printed circuit board is used to fix LCM as shown in the picture below. Attend to the following items when installing the LCM.


- (1) Cover the surface with a transparent protective plate to protect the polarizer and LC cell.



- (2) When assembling the LCM into other equipment, the spacer to the bit between the LCM and the fitting plate should have enough height to avoid causing stress to the module surface, refer to the individual specifications for measurements. The measurement tolerance should be  $\pm 0.1\text{mm}$ .

### Precaution for assemble the module with BTB connector:

Please note the position of the male and female connector position, don't assemble or assemble like the method which the following picture shows



### Precaution for soldering the LCM

	Manual soldering	Machine drag soldering	Machine press soldering
No RoHS product	290°C ~350°C. Time : 3-5S.	330°C ~350°C. Speed : 4-8 mm/s.	300°C ~330°C. Time : 3-6S. Press: 0.8~1.2Mpa
RoHS product	340°C ~370°C. Time : 3-5S.	350°C ~370°C. Time : 4-8 mm/s.	330°C ~360°C. Time : 3-6S. Press: 0.8~1.2Mpa

(1) If soldering flux is used, be sure to remove any remaining flux after finishing to soldering operation. (This does not apply in the case of a non-halogen type of flux.) It is recommended that you protect the LCD surface with a cover during soldering to prevent any damage due to flux spatters.

(2) When soldering the electroluminescent panel and PC board, the panel and board should not be detached more than three times. This maximum number is determined by the temperature and time conditions mentioned above, though there may be some variance depending on the temperature of the soldering iron.

(3) When remove the electroluminescent panel from the PC board, be sure the solder has completely melted, the soldered pad on the PC board could be damaged.

**Precautions for Operation**

(1) Viewing angle varies with the change of liquid crystal driving voltage (VLCD). Adjust VLCD to show the best contrast.

(2) It is an indispensable condition to drive LCD's within the specified voltage limit since the higher voltage then the limit cause the shorter LCD life. An electrochemical reaction due to direct current causes LCD's undesirable deterioration, so that the use of direct current drive should be avoided.

(3) Response time will be extremely delayed at lower temperature than the operating temperature range and on the other hand at higher temperature LCD's show dark color in them. However those phenomena do not mean malfunction or out of order with LCD's, Which will come back in the specified operating temperature.

(4) If the display area is pushed hard during operation, the display will become abnormal. However, it will return to normal if it is turned off and then back on.

(5) A slight dew depositing on terminals is a cause for electro-chemical reaction resulting in terminal open circuit. Usage under the maximum operating temperature, 50%RH or less is required.

(6) Input logic voltage before apply analog high voltage such as LCD driving voltage when power on. Remove analog high voltage before logic voltage when power off the module. Input each signal after the positive/negative voltage becomes stable.

(7) Please keep the temperature within specified range for use and storage. Polarization degradation, bubble generation or polarizer peel-off may occur with high temperature and high humidity.

**Safety**

(1) It is recommended to crush damaged or unnecessary LCDs into pieces and wash them off with solvents such as acetone and ethanol, which should later be burned.

(2) If any liquid leaks out of a damaged glass cell and comes in contact with the hands, wash off thoroughly with soap and water.

**Limited Warranty**

Unless agreed between TRULY and customer, TRULY will replace or repair any of its LCD modules which are found to be functionally defective when inspected in accordance with TRULY LCD acceptance standards (copies available upon request) for a period of one year from date of production. Cosmetic/visual defects must be returned to TRULY within 90 days of shipment. Confirmation of such date shall be based on data code on product. The warranty liability of TRULY limited to repair and/or replacement on the terms set forth above. TRULY will not be responsible for any subsequent or consequential events.

**Return LCM under warranty**

No warranty can be granted if the precautions stated above have been disregarded. The typical examples of violations are :

- Broken LCD glass.
- PCB eyelet is damaged or modified.
- PCB conductors damaged.
- Circuit modified in any way, including addition of components.
- PCB tampered with by grinding, engraving or painting varnish.
- Soldering to or modifying the bezel in any manner.

Module repairs will be invoiced to the customer upon mutual agreement. Modules must be returned with sufficient description of the failures or defects. Any connectors or cable installed by the customer must be removed completely without damaging the PCB eyelet, conductors and terminals.

**■ PRIOR CONSULT MATTER**

1. ①For Truly standard products, we keep the right to change material, process ... for improving the product property without notice on our customer.  
②For OEM products, if any change needed which may affect the product property, we will consult with our customer in advance.
2. If you have special requirement about reliability condition, please let us know before you start the test on our samples.

**■ FACTORY CONTACT INFORMATION**

**FACTORY NAME:** TRULY SEMICONDUCTORS LTD.

**FACTORY ADDRESS:** Truly Industrial Area, ShanWei City,GuangDong,China

P.C: 516600 URL: <http://www.truly.com.hk> <http://www.trulysemi.com>



